

Hog Farming Process and Barn

Field of the Invention

The present invention is directed to livestock farming processes and barns and in particular to processes and barns for raising hogs.

Background of the Invention

In previous hog farming processes, the hogs are raised in barns with slotted floors. The animal waste drops through the slots in the floor and into a pit, which is normally water filled. The pit is emptied into a holding lagoon outside the barn until it is used for spraying on fields. This process has met with public resistance because of the associated odour and appearance of the outside holding lagoon and health concerns over risk of water contamination.

In addition, the hogs were sometimes under stress because of the cold and cramped barn and slotted floors. The slotted floors tend to be damaging to the hogs hooved feet. In addition, drafts and moisture rise from the manure mixture below. These conditions can require that the hogs be administered antibiotics to maintain them in a healthy, docile state.

Summary of the Invention

A hog farming process and barn have been invented that reduce animal stress and effectively handle manure waste without open lagoons.

In one aspect of the present invention, there is provided a barn for raising hogs, the barn comprising: a structure including walls and a roof, a floor within the structure for supporting the hogs, the floor being solid such that materials can settle on the floor without passing therethrough and capable of supporting an animal and the floor including at least one sloped surface and a waste collection area at a lower end of the sloped surface and an animal feeding station providing access to food and water and positioned adjacent an upper end of the sloped surface.

In one embodiment, the barn includes means for creating a temperature differential between an area adjacent the upper end of the sloped surface and an area adjacent the lower end of the sloped surface. The means for creating a temperature differential can be a heater provided to heat an area of the barn adjacent the upper end of the sloped surface. Alternately or in addition, the means for creating a temperature differential is an air circulation system for creating an air draft above the waste collection area.

The animal feeding station is preferably a feeder that contains water in a liquid collection dish. In addition, on-demand means can be provided in the feeder such that food and/or water is released only upon demand of an animal.

In one embodiment, the barn includes at least two sloped surfaces inclining downwardly towards each other and toward the waste collection area. The waste collection area is preferably substantially flat to facilitate waste pick up. Walls can be arranged over the sloping surfaces and the waste collection area to create pens for containment of animals. In one embodiment, the walls have open areas permitting visual communication between the pens. Preferably, these open areas are adjacent the waste collection area.

In another aspect of the present invention there is provided a process for raising hogs, the process comprising: confining hogs on a solid floor, applying compostable, fibrous material to the solid floor, collecting the manure-soiled fibrous material from the floor and composting the manure-soiled fibrous material to form a nutrient rich material.

The fibrous material can be, for example, finely chopped straw, finely chopped newsprint or sawdust. Sawdust is preferred as it also has a pleasant, wood scent that reduces the manure odor within the barn.

In a preferred process, the hogs are confined on a floor that is sloped toward a waste collection area to promote movement of the manure-soiled fibrous material by gravity toward the waste collection area. The floor can additionally include an area conducive to animal sleeping. The process can further include controlling the environment to enhance defecation in the waste collection area.

Brief Description of the Drawings

A further, detailed, description of the invention, briefly described above, will follow by reference to the following drawings of specific embodiments of the invention. These drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. In the drawings:

Figure 1 is a flow chart showing a process for raising hogs according to one aspect of the present invention.

Figure 2 is a perspective view of a hog barn according to another aspect of the present invention.

Figure 3 is sectional view of another embodiment of a hog barn according to the present invention.

Figure 4 is a sectional view through another hog barn according to the present invention.

Figure 5 is a perspective view of a composting facility useful in the present invention.

Figure 6 is a sectional view along line V-V of Figure 4 with a different kind of turning device.

5 Figure 7 is a sectional view along line VI-VI of Figure 4.

Figure 8 is a plan view of a composting structure useful in the present invention.

Figure 9 is a sectional view through another composting structure useful in the present invention.

Detailed Description of the Preferred Embodiments

The invention relates to a process for raising hogs. In addition, in another aspect of the present invention, a hog barn is provided. The barn is particularly suited to carrying out the present process.

Referring to Figure 1, the flow chart shows a process for raising hogs according to one aspect of the present invention. In the present process, hogs are raised in a barn with a solid floor, shown in block 10. A solid floor creates a low stress, comfortable environment for the animals and has little or no effect on their feet. As will be appreciated, solid and liquid wastes, herein termed manure, that are dropped by the animals will accumulate on the solid floor. Fibrous, compostable material such as, for example, sawdust is applied 12 to the barn floor, as by blowing. The sawdust acts as an adsorbent for the animal waste and reduces odor in the barn, replacing the manure odor with a wood scent. Over time, when animals drop waste on the sawdust, a manure-soiled sawdust mixture is formed. The mixture is sticky and more easily removed from the floor, handled and moved than wet, untreated manure. Sufficient fibrous materials should be added such that the resultant manure-soiled mixture is sticky but not saturated with liquid. Applying pressure by hand squeezing should result in a formed mass but should not result in a release of liquid from the mixture.

Occasionally, the manure-soiled sawdust is collected, as indicated in block 14, from the barn floor. The frequency of removal will of course depend on a number of factors including the number of animals, the desired cleanliness of the barn and the amount of sawdust applied to the floor. For best results, the manure-soiled sawdust is removed from the floor at least once per day.

In a preferred embodiment, the barn environment is controlled such that the hogs tend to defecate in a selected area. This facilitates collection of the manure mixture. Environmental controls such as heat and drafts are particularly useful for controlling the area of the barn in which the hogs defecate. In addition, placement of feeders can also be used to control the areas in which the hogs tend to defecate. As will be more apparent with respect to Figures 2 and 3 hereinbelow, controlled defecation can be established by setting up a temperature gradient in the barn. Hogs will tend to defecate in cool, drafty conditions and away from feeding areas and bedding areas, which can be defined by heating an area of the barn.

As indicated in block 16, after collection the manure-soiled fibrous materials are composted to produce a nutrient-rich product substantially free of the harmful bacteria normally associated with manure. In a preferred embodiment, the composting process is conducted in an enclosed area such as another area of the barn or another building. An enclosed area is preferred as the composting process can be controlled and protected from the elements to increase efficiency of the process, and confined, reducing objectionable appearances and odours, over open systems. Saleable and substantially odourless compost is produced from the soiled sawdust. The compost is suitable for use as a potting soil or a soil supplement.

Preferably the composting step is carried out using a continuous throughput process. A composting structure that is particularly useful in a continuous process is described with respect to Figures 5 through 9, hereinafter.

Referring to Figures 2 and 3, a barn according to another aspect of the present invention is shown. While the barn is particularly useful for housing at least a portion of

the process described in Figure 1, it also provides a low stress environment for raising hogs.

The barn includes a roof 20, walls 22 and a floor 24. Various roof and wall structures can be used and are not particularly relevant to the present invention. In hog farming, it is generally accepted that the hogs be housed in a structure that protects the animals from the elements and provides a controlled environment.

Floor 24 is solid; being without the slots or openings normally associated with hog barn floors. In particular, floor 24 is solid such that materials, such as manure 25, which settle on the floor are supported thereon and will not pass therethrough. The floor is also capable of supporting a plurality of hogs. The floor can be, for example, formed of concrete.

The floor includes two sloping planar surfaces 26 that are inclined downwardly toward each other. While the barns illustrated in Figures 2 and 3 each have two sloping surfaces 26, it is to be understood that a barn could contain any number of sloping surfaces such as for example, one or four. A schematic view of a floor 24a having four sloping surfaces is shown in Figure 4. In one preferred embodiment, the sloping surfaces have a 3.0 to 3.5% slope.

Between sloping surfaces 26 is a waste collection area 28. The waste collection area of floor 24 is solid and can support hogs, although in some embodiments it may be fenced to prevent access thereto by the hogs. To facilitate pick-up of the waste, area 28 is flat, open and accessible. In the illustrated embodiment of Figure 2, the waste collection area is formed as a flat-bottomed gutter. Sides 29 of the gutter facilitate containment of the waste and pick-up. However, it is to be understood that the area can take other forms, as shown in Figure 3, and need not be level. The waste can be picked up in various ways. However, preferably a small tractor, such as a Bobcat™, carrying a bucket is used. Thus, preferably the waste collection area is sized and positioned in an elongate configuration, along the length of the barn, to facilitate travel therealong by the tractor.

Animal feeding stations 30 are disposed about floor 24. The feeding stations are spaced from waste collection area 28 a sufficient distance to accommodate the animals on sloping surfaces 26 between area 28 and feeding stations 30. In a preferred embodiment, feeding stations are positioned adjacent the upper end of the sloping surfaces a maximum distance away from the waste collection area. To increase cleanliness of the barn floor adjacent the feeders, the feeders are preferably selected to contain water rather than allowing it to spill onto the floor. Not only does this enhance cleanliness, it limits the floor from getting wet and is beneficial since pigs tend to drop waste in wet areas. A particularly useful feeder includes a liquid collection dish and, preferably also, an on-demand switch such that food and water are released only upon demand of an animal. Groba™ wet/dry feeders available from the Netherlands are particularly useful.

A heater such as for example an in-floor hot water system 32 (Figure 2) or a radiant overhead heater 34 (Figure 3) is installed to heat the upper end of sloping surfaces 26 to tend to cause the animals to congregate and sleep around the upper ends of the sloping surfaces, rather than near or in waste collection area 28. By heating the area at the upper end of the sloping surfaces, the area around the waste collection area is to be relatively cooler. An in-floor hot water system with heated water flowing through pipes 36 embedded in or under floor 24 is preferred for control, safety and efficiency. This heating may not be required in times of the year when outside temperatures are quite warm.

An air circulation system is mounted to direct a draft, indicated by arrows 37, towards the waste collection area. The draft should be directed toward waste collection area 28 such that it impinges that area and possibly the lower end of the sloped surfaces first. This provides that the draft in these areas is cooler and stronger than in other areas of the barn floor. In particular, although air after it impinges the floor in these areas will be redirected to other parts of the barn, that air will be increasingly warmed and diffused.

The air circulation system can include one or more air ducts 38a, 38b with apertures 40, baffles 41 or other means arranged so that air passing therethrough is directed

generally toward waste collection area 28. Air is blown through the air ducts and out through the apertures to cool the area around the waste collection area. Mistlers 39 can be provided to enhance cooling within the barn. Mistlers 39 release atomised water particles into the air. If the temperature in the barn rises to values of, for example, greater than 28°C, the mistlers 39 will be activated to release moisture into the air that will bring the temperature down inside the barn. Preferably, the mistlers are located adjacent apertures in the ducts so that the mist can be circulated with the air and directed first to area 28.

Walls 42, 43 define pen areas and can be arranged in various ways, as desired. For the healthiest, lowest stress environment, a pen should provide at least 11 square feet of space per 250lb animal. This also promotes a proper dunging pattern. Generally it is not desirable for a pen wall to extend sideways across a sloping surface, but rather with the incline on the sloping surface so that each pen extends from the upper end of the sloping surface to the lower end thereof. Walls 43 can extend to restrict access of the hogs into waste collection area 28, if desired. However, if such walls 43 are present, they must be raised off the floor or include openings to permit waste to pass thereunder into area 28. Closable gates 44 can be provided through the walls for ease of access. Where walls extend through area 28, gates 44 should be positioned to allow clear access along the waste collection area for ease of manure pick-up.

Walls 42, 43 can be solid. Alternately, walls can be open (i.e. constructed of fencing) to permit visual contact by hogs between pens. In a preferred embodiment, walls 42' are solid adjacent feeding stations 30 and heated areas while open walls 42" are positioned adjacent waste collection area 28.

While the barn creates a low stress environment and promotes dunging in a selected area indicated as 45 in or near the waste collection area, to facilitate pick up of manure, to absorb odor and to increase comfort and cleanliness for the animals, fibrous material 46 is applied to the floor, as discussed with respect to Figure 1. The fibrous material is preferably applied at the upper ends of the sloping surfaces. Over time it will become

soiled with manure and be moved towards waste collection area 28. The manure-soiled fibrous material collected from the barn is particularly suited to composting.

A number of factors function to create the favourable conditions in the barn. First by sloping the floors of the barn, waste tends to flow by gravity and by displacement by foot traffic and movement of the hogs about the floor. The amount of fibrous materials applied to the upper end of the sloped surfaces is a significant factor in how fast the manure flows toward area 28. The greater the amount of sawdust used, the faster the manure will be moved off the sloped surfaces. The appropriate amount of sawdust to be used can be determined as discussed in Figure 1 and care should be taken to ensure that the sawdust is not too wet or too dry when it gets to the waste collection area. In addition, hogs are relatively intelligent and will not defecate near their feeding and sleeping areas. Thus, placement of heated areas and feeding areas away from the waste collection area will increase the tendency of the hogs to defecate in area 28. Cool drafts will also increase the tendency for pigs to defecate. Thus, by directing a flow of air toward area 28, defecation in that area will be increased. Finally, as is known visual contact between hogs in separate pens may cause defecation. Thus, provision of open fencing 42" adjacent the waste collection area further enhances waste accumulation in that area.

Thus, the barn creates an environment where manure tends to be dropped in a selected area, rather than over the entire barn floor and the hogs tend not to sleep or feed in manure-soiled areas. As noted previously, to increase floor cleanliness feeding stations can be selected that control liquid spills and the release of food and water.

A composting structure has been invented to efficiently handle the manure generated from a livestock operation. The structure is shown in Figures 5 to 9. This structure is preferably contained in an enclosure to avoid interference by precipitation and wind and to keep the livestock operation clean and substantially odor-free. While the term manure is used herein to describe the material handled by the compost structure, it is to be understood that the material handled by the composter can be dry or sticky manure,

manure-soiled fibrous materials or animal carcasses. These materials, after passing through the structure will become nutrient-rich compost.

5 The composting structure contains the manure and moves it through a 25 to 30-day composting process. Air or oxygen is injected into the manure at regular periods to enhance composting. In particular, the structure has a pair of substantially parallel containment walls 50 extending between two open ends 52, 54. One end 52 is the manure input end and the other 54 is the compost output end. The manure pile 55 rests on floor 56 between the walls and is moved from the input end to the output end over a 25 to 30-day period with aeration and mixing. The walls must be long enough to accommodate 25 to 30 days worth of manure, while allowing for addition of manure to the input end each day. In one exemplary livestock operation, an amount of manure is added to the pile each day that adds 10 linear feet to the pile and the process takes 25 days. Thus the walls are about 250 feet long (10 feet per day x 25 days).

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10

bacteria continue to work in the pile. Composting occurs optimally when manure temperature stays above 55°C. Thus, when the temperature drops it is indicative that the bacteria are not working effectively. Therefore, preferably, a temperature probe 66 is installed in the structure to determine pile temperature. A thermostat 68 is in communication with the probe to initiate operation of the aeration system, as by opening valves 69 or activating a fan 70, when the temperature of the pile falls below a selected temperature.

The air supply pipes are elongate with regularly spaced nozzles 72. Nozzles 72 can inject air upwardly or downwardly depending on the floor surface construction.

Air supply pipes 62 are positioned out of the way of the turning device, below the effective surface of floor 56. In one embodiment, pipes 62 are positioned in a gravel-filled pit 74 or gravel-filled channels below the effective floor surface between the walls. To avoid getting gravel 78 in the manure, and therefore in the final compost, a layer of cedar bark mulch 80 can be laid above gravel 78. This cedar bark or gravel would be scraped down to a level below the turning device and effectively become an undisturbed floor surface over time.

The pipes 62, gravel 78 and mulch 80 can be replaced by pipes 82 mounted in cement channels 84 in floor 56. Pipes 82 include upwardly directed nozzles 72. This provides a more supportive surface than the gravel and allows equipment to be moved thereover for cleaning, etc. Channels 84 can be filled with pea gravel 86 or other coarse granular material to prevent manure from being caught therein.

The ends 52, 54 are open and at floor level so that the manure can be loaded into the input area and removed from the output area by riding in with a tractor.

It will be apparent that many other changes may be made to the illustrative embodiments, while falling within the scope of the invention and it is intended that all such changes be covered by the claims appended hereto.